

PROTECTA Series

Weatherproof switches and sockets - IP66

CONTROL DEVICE


REFERENCE STANDARDS




EN 60669-1
Switches for household and similar fixed-electrical installation.
Part 1: general requirements.

VERSIONS

TECHNICAL CHARACTERISTICS

- 

One way switch single pole
- flush mounting
- surface mounting
- 

Bell push switch single pole
- flush mounting

Rated current:	10A-10AX-20A-20AX
Rated voltage:	250V~
Frequency:	50Hz
Insulating voltage:	250V~
Protection degree:	IP66
Operating temperature:	-20°C +60°C
Cabling capacity of the terminal:	3x2,5mm² 2x4mm² 1x6mm²
Glow Wire test:	650°C/850°C
Halogen free:	Yes
Material:	Engineering plastic
Cable inlet:	M20
Colour:	Grey RAL 7035
LED colour:	Orange

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited Resistance	Resistant	Limited Resistance	Resistant	Resistant	Not Resistant	Not Resistant	Resistant	Limited Resistance	Resistant

CONTROL DEVICES M95 (95x95mm)



Description		FLUSH MOUNTING		SURFACE MOUNTING	
One way switch single pole	1 gang 10AX - 250V~ 1/12	137.3011		137.5011	
One way switch single pole	2 gang 10AX - 250V~ 1/12		137.3021		137.5021
Bell push switch single pole "BELL"	1 gang 10A - 250V~ 1/12			137.3311B	

- Flush mounting: box not included.

SWITCH SOCKET OUTLETS



Description	Dimensions	FLUSH MOUNTING	SURFACE MOUNTING
15A - 250V~ S.P. switch	M115 (115x115mm) 1/12	137.4111	137.6111

- Flush mounting: box not included.